

Escene ES220 series is a popular type IP Phone in SayHi phones series, with modern design, functional, practical and voice clarity characteristics. It implements the rich-feature by cooperating with the communications platform, such as call transfer, hotline, multi-party conferences, voice mail, interruption-free, etc.

Key Features

- ► HD Voice: HD Codec, HD Speaker, HD Handset
- Convenient and fast for Installation and maintenance
- ► Multi-Language :Chinese,English,French,Russian,etc.
- Support HTTP/TFTP/Telnet/Auto provision, and TR069 centralization maintenance
- ▶ 10 programmable keys ,Configuration for speed dial, hotline etc.
- ► Two SIP accounts and support three-way conference, SMS
- Enterprise Phonebook, LDAP Phonebook



ES220 Technical Datasheet

► Phone Features

- •2 sip accounts, Hotline
- •Call hold, Call waiting, Call forward, Call return Call transfer (blind/busy/ask)
- •Caller ID display, Redial, Mute, DND
- •Auto-answer, 3-way conferencing
- •Speed dial, SMS, Voicemail
- •Message Waiting Indication LED
- •Tone scheme, Volume control
- •Direct IP call without SIP proxy
- •Ring tone selection/import/delete
- •Phonebook (Personal Phone Book search input/output TTL 300 entries)
- •Black list
- •Hand-free indicator
- •One-key back ©
- •Call history: dialed/received/missed(50 entries)
- •Multi-Language
- •Multi-Language
- •Programmable Soft Keys, Supports PC control •Support switching SIP server & Second server

► Advanced Features

- •XML Phone Book search and input & output
- •Enterprise phone book(800 entries)
- LDAP phone book
- •Functions customizable keys

► IP PBX System Integration

Busy lamp field (BLF), BLF list
Bridged line appearance (BLA)
DND & Forward synchronization
Intercom, Paging, (MoH)
Call pickup, Dial Plan, Call recording

► Compatible with the platform

•Anonymous call, Anonymous call rejection •Network conference, Distinctive ringtone

►Security

LLDP, VLAN QoS (802.1pq),VPN(L2TP)
Transport Layer Security (TLS)
Digest authentication using MD5/MD5-sess
Secure configuration file via AES encryption
Phone lock for personal privacy protection
Admin/User 2-level configuration mode
Network Features

•SIP v1 (RFC2543), v2 (RFC3261) •DNS SRV (RFC3263) •NAT Traversal: STUN mode •DTMF: In-Band, RFC2833, SIP Info, Auto •HTTP/HTTPS Web Management •IP Assignment: Static/DHCP/PPPoE •Bridge/Router mode for PC port •TFTP/DHCP/PPPoE client •DNS client, NAT/DHCP server •Ipv4

►Management

•Auto-provision via FTP/TFTP/HTTP/HTTPS •SNMP V1/2 , TR069 •Configuration: browser/phone/autoprovision •Trace package and system log export

► Codes and Voice Features

•Wideband Codec: G.722 •Narrowband codec: G.711µ/A, G.723.1 G.726, G.729AB,iLBC •VAD, CNG, AEC, AGC •Full-duplex,

► Physical Features

128x32 graphic LCD
27 keys including 2 programmable keys
6 LEDs: 1xstatus light, 1xspeaker light 2xaccounts lights, 1x message light,
1x neadset light.
1x RJ-9 handset port
2xRJ45 10/100M Ethernet ports
Power adapter: AC 100~240V input and DC 5V/1A output
Power over Ethernet ,IEEE 802.3af,class 0
Power consumption: 2.5-3.5W
Net weight: 1.07KG
Dimension: 206x166x59MM
Operating humidity: 10~95%
Storage temperature: up to 60°C

▶Package

•Qty/CTN: 10 PCS •Carton Meas: 480x380x390MM Measurement: 0.065CBM(0.5% more or less) N.W/CTN: 11KGS G.W/CTN: 12KGS

► Certifications









Escene Communication Co.,Ltd

Address: Floor 4 Building C YueAn Industrial Park No.51 Huangcun Road Tianhe District, Guangzhou, China. Postal Code: 510665 Tel: (+86)20-28096798 Fax:(+86)20-28096786